

D180 CONTACTLESS mPOS





LASSIC



Monitor







www.pax.com.cn



SPECIFICATIONS

୍ବ	Operating System	Monitor
٢	Processor	32-bit ARM CPU
	Memory	128KB SRAM + 1MB Flash External Storage: 4MB Flash
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
Ū	Display	128 x 64 Pixels LCD
((†))	Comms Configurations	Bluetooth® 4.2
*	Battery	250mAh 3.7V
Ę	Keys / Buttons	13 Keys: 0~9 3 Function Keys
八沙	Audio	1 Buzzer
	Ports	1 micro-USB 2.0
[0]	Physical	116 x 59.6 x 13 mm, 83g (including battery)
G	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 96% Relative Humidity, Non-condensing
ଞ	Accessories	1 USB Cable
\bigcirc	Certifications	PCI PTS 5.x, SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless American Expresspay Discover D-PAS Mastercard TQM Interac Flash L2 NSICC L2 ABECS UL CE FCC Anatel RoHs IC







This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX and the PAX logo are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. The **Bluetooth®** word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Limited is under license. Other trademarks and trade names are those of their respective owners. © 2022 PAX Technology Limited. All rights reserved.

